



# Shell Rimula R1 Multi 20W-40

- Reliable Lubrication

## Heavy Duty Diesel Engine Oil

Uses proven performance additives to fight engine wear providing reliable lubrication.



### Performance, Features & Benefits

- **Reliable Performance**  
Provide reliable all-year-round performance in the applications for which they are intended.

- **Moderately rated diesel engines**  
Shell Rimula R1 oils are for use in less powerful diesel engines, such as those found in small trucks, commercial vehicles, vans, tractors and certain stationary units.

### Main Applications



### Specifications, Approvals & Recommendations

- API CC, SC  
For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

### Typical Physical Characteristics

Properties			Method	Shell Rimula R1 Multi 20W-40
Kinematic Viscosity	@40°C	cSt	ASTM D445	110
Kinematic Viscosity	@100°C	cSt	ASTM D445	14.4
Viscosity Index			ASTM D2270	128
Density	@15°C	kg/l	ASTM D4052	0.894
Flash Point (COC)		°C	ASTM D92	240
Pour Point		°C maximum	ASTM D97	-18

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

### Health, Safety & Environment

- **Health and Safety**  
Shell Rimula R1 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.  
Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.  
Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

- **Protect the Environment**  
Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

### Additional Information

- **Advice**  
Advice on applications not covered here may be obtained from your Shell representative.