



# Shell Rimula R6 MS 10W-40

- Maintenance Saving

## Fully Synthetic Heavy Duty Diesel Engine Oil

Shell Rimula R6 MS fully synthetic oils deliver highly responsive protection, maintenance saving long drain performance, protection against soot, wear, deposits and fuel economy. Suitable for most Euro 4, 5 engines and Euro 6 Scania engines.



### Performance, Features & Benefits

- **Maintenance Saving**

Shell Rimula R6 MS meets the long oil drain requirements of leading engine makers such as Mercedes-Benz, MAN, DAF, Volvo and others to allow operators to optimize maintenance scheduling and maximize equipment availability without compromising durability.

- **Exceptional Piston Cleanliness**

Shell Rimula R6 MS use advanced additive technology that builds on the reputation and performance of Shell Rimula engine oils for high levels of piston cleanliness essential for long engine life.

- **Low Wear -Long Engine Life**

Shell Rimula R6 MS meets the demanding wear protection of many European, American and Japanese engines, controlling bore polish and valve train wear thus maximising engine life.

- **Fuel Economy**

Shell Rimula R6 MS can save money in fuel consumption compared to high viscosity grades.

Also meets or exceeds the performance requirements of other European makers such as Volvo, Renault, DAF, Scania, Deutz and Iveco as well as Cummins, Mack and many Japanese engine types Not recommended for Caterpillar engines.

- **Low Emission Engine Use**

Shell Rimula R6 MS meets the requirements of most European manufacturers for Euro 2,3 engines and most Euro IV and Euro V engines without Diesel Particle Filter as well as Euro VI engines of Scania.

For enhanced performance and protection of the latest low emission engines, we recommend the use of our advanced low-emissions products, Shell Rimula R6 LM/LME.

### Specifications, Approvals & Recommendations

- ACEA E7, E4
- Deutz DQC IV-10
- IVECO T3 E4 (Meets Iveco Specification)
- MAN M3277
- MB-Approval 228.5
- MTU Category 3
- Renault trucks RXD
- Scania LDF-2 / LDF-3
- Volvo VDS-3

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

### Main Applications



- **On-highway Heavy Duty Applications**

Particularly suited for a wide range of trucking and transportation applications in vehicle using modern low-emission engines from Mercedes-Benz and MAN.

### Typical Physical Characteristics

Properties			Method	Shell Rimula R6 MS 10W-40
Kinematic Viscosity	@40°C	mm <sup>2</sup> /s	ASTM D445	90.0
Kinematic Viscosity	@100°C	mm <sup>2</sup> /s	ASTM D445	13.6

Properties			Method	Shell Rimula R6 MS 10W-40
Dyn. Viscosity	@ -25°C	mPa s	ASTM D5293	6600
Viscosity Index			ASTM D2270	153
Total Base Number		mgKOH/g	ASTM D2896	15.9
Sulphated Ash		%	ASTM D874	1.9
Density	@15°C	kg/l	ASTM D4052	0.867
Flash Point (COC)		°C	ASTM D92	240
Pour Point		°C	ASTM D97	-42

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

## Health, Safety & Environment

### • Health and Safety

Shell Rimula R6 MS 10W-40 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Additional Information

### • Advice

Advice on applications not covered here may be obtained from your Shell representative.